

# ATS-2p

field  
telephone

always, in all conditions ...

**ISO 9001**



 **TELKOM** S.A.  
**TELOS**

# ATS -2p

FIELD TELEPHONE

The field telephone ATS – 2/p type is an analogue terminal telephone. It is designed to provide communication in the field communication objects on all the commanding levels, in the telephone channels of natural voice band.

The telephone can work with each type of telephone exchange in two-wire circuit communication arrangement and with special circuits in four-wire mode.

The telephone meets the requirements for the implements of N 7 UZ-II (A and B) group, according to WPN-84/N-01003 standards, in the operating temperature ranging from  $-20^{\circ}\text{C}$  to  $+65^{\circ}\text{C}$ .

## BASIC PROPERTIES OF THE TELEPHONE:

- electrohermetic, electromagnetic information leakage-proof casing;
- continuous, 24 hour work capability;
- in idle mode, both the transmission and reception circuits can be disconnected from the telephone line;
- optical and acoustic call signal, ring volume control;
- protection from unauthorised usage – when the telephone is locked, both the keyboard and the microtelephone circuits are disconnected;
- the possibility to disconnect the microphone using the "tangenta" switch mounted on the microtelephone;
- dialling the subscriber's number using the keyboard that can be switched from decadic to DTMF mode;
- a possibility to use the direct access dialling option of 10 numbers stored in the memory and activated with individual keys;
- last number redial option;
- the generator of line state control pulses – when the microtelephone is replaced.

## TECHNICAL PARAMETERS

Transmission reference equivalent:	$-4 \div +6$ dB
Receive reference equivalent:	$+3 \div -10$ dB
Sidetone attenuation:	min. 7 dB
Ring loudness:	min. 80 dB
Power supply from the central battery:	60 V 2 x 500 $\Omega$ ; 50V 2 x 400 $\Omega$ or 46 V $\pm$ 20 % 2 x 300 $\Omega$
The telephone weight:	2,3 kg
Dimensions:	270 x 150 x 101 mm



ISO 9001:2000 AQAP 2110:2006  
QUALITY SYSTEM

30-003 Kraków, ul. Lubelska 14-18  
Sales Department:  
tel. (012) 631 06 30, (012) 633 02 00, fax (012) 631 06 31  
e-mail: [handlowy@telos.com.pl](mailto:handlowy@telos.com.pl)  
[www.telos.com.pl](http://www.telos.com.pl)